HIGH PERFORMANCE MODULAR LED FLOODLIGHT



LF90 - 2 SERIES







Key Features

- Available in 100-240VAC
- Triac Dimming Compatible
- Rapid heat-dispensing design to prolong lamp life and optimise lumen output
- Long service life of >50,000 hours L70 @ 50°C (Ta)
- Compact and lightweight design
- Safety, EMC and IEC compliance





Application


Decks, Marinas, Docks, Ports, Warehouses

Material


Marine grade aluminium alloy with powder coating, comes with 4mm tempered glass front cover


Weight


8.6Kg



[mm]







TECHNICAL SPECIFICATIONS





Subject to Replacment based on Projection Distance:









Туре	Modules	Beam Angle (50%)	Beam Angle (10%)	Power	ССТ	Ambient Temp (Ta)	Lumen	CD	Projection Distance	Illum. Area (Diameter)
									@200 Lux	
LF90N02A34	2M-N	17°	32°	180W	5000K	-40°C ~ +50°C	22800lm	193600cd	31.1m	9.3m
LF90M02A34	2M-M	45°	87°	180W	5000K	-40°C ~ +50°C	21600lm	28000cd	11.8m	9.8m
LF90F02A34	2M-F	105°	148°	180W	5000K	-40°C ~ +50°C	23400lm	9000cd	6.7m	17.5m

Also available in other CCT and beam angle upon request.